

TITLE: GASKETLESS DRUMBACKGROUND OF THE INVENTIONField of the Invention:

[0001] This invention relates to drums made of synthetic resins and more particularly to such plastic drums that can be sealed by a gasketless lid or cover so as to prevent air and water vapor from entering the closed drum.

Brief Description of the Prior Art:

[0002] Drums and similar containers made from synthetic resin have come to be used extensively in storage and shipment of granular materials of all types. Such drums are inexpensive, durable, and corrosion resistant. Open-head drums of this type are generally provided with a circular rim or chime at the open upper end. Such drums are closed with a separate cover or lid that is clamped to the chime of the drum. Conventionally, the lid is provided with a gasket that engages the chime to form a seal. The gasket is typically made of a synthetic resin that is somewhat softer than the body of the drum and the lid in order to conform exactly to the upper edge of the chime.

[0003] Such drums having gasketed lids are generally satisfactory for storage and transportation of materials. However the use of gaskets to form a seal between the lid and the chime has certain drawbacks. The separate manufacture of a gasket requires an assembly step in the manufacture of the drum cover, which increases the cost of manufacture. In some cases the relatively soft gasket material may permit the passage of water vapor through the seal, as well as contaminate the product packaged if it becomes torn or abraded.

[0004] Accordingly, a need has continued to exist for a drum lid or cover that does not suffer from the disadvantages of a gasketed drum lid.

FO9020-0255860

SUMMARY OF THE INVENTION

[0005] The deficiencies of conventional gasketed drum covers have been alleviated by the gasketless cover of the invention. According to the invention a reusable sealable plastic drum comprises

a plastic drum body with a convex upper chime having a convex chime radius,
a plastic lid having an annular, peripheral mating channel sized to accept the upper chime, the channel having an inner wall, an outer wall, a mouth for receiving the upper chime, and a base surface for engaging the upper chime, the base surface having a concave radius, which is matched to the convex chime radius, and

a lockband surrounding the outer wall, whereby tightening of the lockband causes the concave base radius to fully engage the convex chime radius in a sealing relationship.

[0006] Accordingly, it is an object of the invention to provide a sealable plastic drum.

[0007] A further object is to provide a sealable plastic drum having a lid or cover that does not contain a sealing gasket.

[0008] A further object is to provide a gasketless sealable plastic drum having good resistance to permeation of water vapor.

[0009] A further object is to provide a gasketless sealed drum eliminating the possibility of contamination due to abrasion, tearing, flaking or cutting of gasket material.

[0010] Further objects of the invention will be apparent from the description of the invention which follows.

BRIEF DESCRIPTION OF THE DRAWINGS

[0011] Figure 1 is a side elevational view, partly cut away, of the drum of the invention.

[0012] Figure 2 is a cross-sectional view of the portion of the drum chime and gasketless lid that forms the seal, indicated by the circle 2 in Figure 1.

[0013] Figure 3 is a cross-sectional view of another embodiment of the invention incorporating an auxiliary sealing gasket compressed by the heel of the outer wall of the drum lid.

050305Z - 020101

[0017] In order to provide a good seal, the width of the top of the chime 110 should be great enough to provide a relatively large area of contact between the upper surface 112 of the chime 110 and the base 124 of the peripheral channel 118. Preferably the width of the top of the chime 110 (top width) is about 0.190 inch (4.83 millimeters). However the skilled practitioner will realize that the width of the top of the chime 110 may be somewhat greater or less than this

specific width, so long as the convex curvature of the upper surface 112 of the chime 110 is closely matched to the concave curvature of the base 124 of the peripheral channel 118, and that the width is great enough to provide a satisfactory seal.

[0018] If additional sealing security is desired, the drum may be provided with an auxiliary compressible sealing ring 132, as shown in Figure 3, located at the inner edge of the drum flange 108. When the lockband 130 is tightened, the heel 128 of the cover compresses the sealing ring 132 to form an additional seal.

[0019] The drum and lid of the invention may be made of any suitable plastic material. Synthetic resins such as high-density polyethylene and polypropylene are suitable for making the drum body and lid. The lockband may also be made of a plastic material provided it has sufficient strength to exert the requisite compressive force on the drum flange. A conventional metal lockband can also be used. The drum body 102 and lid 114 can be manufactured by conventional molding techniques suitable for the synthetic resin of which the drum body and lid are made.

[0020] The invention having now been fully described, it should be understood that it may be embodied in other specific forms or variations without departing from its spirit or essential characteristics. Accordingly, the embodiments described above are to be considered in all respects as illustrative and not restrictive, the scope of the invention being indicated by the appended claims rather than the foregoing description, and all changes which come within the meaning and range of equivalence of the claims are intended to be embraced therein.

FO9040 026680